

Customized Completion Solutions

When well performance and profitability are truly your priority, GEODynamics TECHNIK™ Solutions offer the ultimate custom-fitted answer. From initial review, through system optimization, to deployment and analysis, our technical specialists work seamlessly with your asset development team to engineer a completion solution for your unique reservoir and well conditions. Consult your GEODynamics representative for details.

CONNEX REACTIVE PERFORATING **Reactive® Perforating Technology**

System Size inches	Product Name	Part Number	Shot Density per foot	Phasing degrees	Qualified For Shooting		Explosive Load		Casing Size inches	Entrance Hole inches	Penetration inches test
					In Fluid	Dry	grams	explosive			
2	2007 CONNEX®	EC2-20A0722-RC	6	0 / 60 / 90	✓		6.8	HMX	2 7/8	0.26	Use penetration data for equivalent RAZOR® Extra Deep Penetrating charge
2	2007 CONNEX® XLS	EC2-20B0722-RC	6	0 / 60 / 90	✓	✓	6.5	HMX	2 7/8	0.26	
2 3/8	2311 CONNEX®	EC2-23A1122-RC	6	60	✓		11.0	HMX	3 1/2	0.35	
2 1/2	2511 CONNEX®	EC2-25A1122-RC	6	60	✓		11.5	HMX	3 1/2	0.34	
2 7/8	2715 CONNEX®	EC2-27A1522-RC	6	60	✓	✓	15.0	HMX	4 1/2	0.39	
2 7/8	2715 CONNEX® XEH	EC2-27A1542-RC	6	60	✓	✓	15.0	HMX	4 1/2	0.44	
2 7/8	2818 CONNEX®	EC2-28A1822-RC	6	60	✓		18.0	HMX	4 1/2	0.45	
3 1/8	3319 CONNEX® XEH	EC2-33A1942-RC	6	±30 LS / 60 / 180	✓	✓	19.0	HMX	4 1/2	0.52	
3 1/8	3323 CONNEX®	EC2-33A2322-RC	6	±30 LS / 60 / 180	✓		22.7	HMX	4 1/2	0.46	
3 1/8	3323 CONNEX® XEH	EC2-33A2342-RC	6	±30 LS / 60 / 180	✓		22.7	HMX	4 1/2	0.56	
3 3/8	3323 CONNEX®	EC2-33A2322-RC	6	±30 LS / 60 / 180	✓	✓	22.7	HMX	4 1/2	0.47	
3 3/8	3325 CONNEX®	EC2-33B2522-RC	6	±30 LS / 60 / 180	✓		25.0	HMX	4 1/2	0.48	
3 3/8	3325 CONNEX® XEH	EC2-33B2542-RC	6	±30 LS / 60 / 180	✓		25.0	HMX	4 1/2	0.54	
4	4039 CONNEX®	EC2-40A3922-RC	4	60 / 90	✓		39.0	HMX	5 1/2	0.49	
4 1/2	4039 CONNEX®	EC2-40A3922-RC	5	60	✓		39.0	HMX	7	0.46	
4 1/2	3323 CONNEX®	EC2-33A2322-RC	12	135-45	✓		22.7	HMX	7	0.40	
7	4039 CONNEX®	EC2-40A3922-RC	12	135-45	✓		39.0	HMX	9 5/8	0.44	